

High Gloss By 1 Coat Spec General Solvent Base 2K Paint

# 『PLANET PZ-Ⅱ』

#### **♦**Feature

- 1) High gloss, high image clarity
  It has better gloss and image clarity than
  conventional one-coat metallic paint.
- 2) Weathering resistance Excellent gloss retention rate, stain resistance and resistance to discoloration.
- 3) Recoatability
  Good overcoatability.

### **♦**Standard Coating Specification

Item	Coating Specification					
Standard Hardener	POLYHARD Z-50					
Mixing Ratio	Paint/Hardene	r/Thin	ner :	40 /	10 /	20
Viscosity		1	0 ^	~ 13	sec.	
	Ford cup #4				20	Ŝ
Standard Film Thickness			25	μm		
Flush Off Condition	Approx		5	min.		
Standard Drying Conditions	80	°C	×	30	min.	

#### **♦**Applicable Substrate / Standard Thinner

Substrate	Standard Thinner
ABS	
AES	PLANET THINNER #743 PLANET THINNER #D260
РММА	

<b>♦</b> Coating Film	Substrate: ABS
Performance	Substrate . ADS

Test Item	Result	Test Condition	
Pencil hardness	ОК	Mitsubishi Uni (HB or higher)	
Adhesion	100/100 OK	1mm cross-cut Peeling by cellophane adhesive tape	
Water resistance	100/100 OK	40°C hot water × 240h immerison Adhesion test	
Humidity resistance	100/100 OK	50°C∙98%RH×240h Adhesion test	
Impact resistance	ОК	Du Pont impact tester 1/2 inch 500gf × 30cm	
Gasoline resistance	ОК	Regular gasoline 20°C × 30min.	
Volatile oil resistance	ОК	No.1 volatile oil 20°C × 24h immersion	
Print resistance	ОК	Gauze、70°C × 2h 500gf、Φ40mm	
Recoatability	ОК	$\begin{array}{c} \text{Painting} \rightarrow \text{drying} \rightarrow \\ \text{Leave at room temperature for 7} \\ \text{days} \rightarrow \text{Overcoating} \end{array}$	
Accelerated weathering resistance	ОК	SWOM 1000h	

## **♦**Application / Adoption History

- •Interior and exterior applications for automobile
- •Home appliance,consumer electronics and telecommunications
- Optical instruments
- Architectures and construction materials
- Industrial equipments
- ●Please dilute this paint with exclusive thinner, then thoroughly stir and use filtration.
- Coating specification may change depending on the material grade, type and spraying equipment.
- The film performance is evaluation results under our company's standard specification, and it is not a guarantee for all the results.
- ●Please contact our Sales Dept. as below if you have any inquiries or questions

Contact: Origin Co., Ltd. Chemitronics Div. Sales Dept. Tel: +81-42-557-4113